

## Features & Benefits

### Features

### Benefits

Translucent (i.e. semi-transparent) finish.	Highlights the natural features of the timber.
Weathers by gradual erosion of the finish, rather than peeling or flaking.	Preparation at maintenance normally only requires thorough cleaning, thus reducing overall costs.
Contains a mould inhibitor and fungicides.	Prevents disfiguration of the finish due to mould growth, surface fungi and blue stain.
Contains a resin to fix the active ingredients in the coating.	The finish is water repellent, with no risk of active ingredients being leached out.
Low viscosity formulation.	Ideal for quick application to large surface areas (facades, fascias and fences) without the risk of brush marks.

## GORI 44

**Product Range**  
 7802 Pine  
 7804 Teak  
 7805 Oak  
 7807 Dark Oak  
 7808 Walnut  
 7809 Redwood  
 7810 Palisander  
 7811 Ebony  
 8504 Swedish Red  
 8715 Light Blue  
 9900 Clear

<b>Product</b>	<b>GORI 44</b>
<b>Content</b>	Alkyd resin dissolved in white spirit
<b>Colour</b>	Coloured for outdoor application
<b>Finish</b>	Translucent. Matt to semi-gloss sheen
<b>Application Rate</b>	8-10 m <sup>2</sup> on smooth planed hardwood
<b>Application</b>	Approximately 30 µm per coat minimum w.f.t.
<b>Volume Solids</b>	Approximately 24%
<b>Drying Time</b>	3-5 hours (touch-dry), 12-24 hours (recoatable)
<b>Flash Point</b>	62°C
<b>Density</b>	0.8 ± 0.2 g/ml
<b>Cleaning</b>	White spirit
<b>Packing</b>	0.75, 5, 15 and 200 litres
<b>Storage</b>	Above 5°C. Shelf life 24 months in unopened can

### System treatments – softwood and hardwood

## Recommended Specification

Area of application	Primer	Intermediate	Top coat
Facades, fascias and fences	GORI 44 all round before installation	1 coat GORI 44	1 coat GORI 88
Windows and Doors	GORI 44 all round before installation	1 coat GORI 88	1 coat GORI 88

Natur Woodcare (M) S/B  
 21, Jln. PJS 11/7,  
 Bandar Sunway,  
 46150 P.Jaya, Selangor.  
 Tel: +603 5632 3272  
 Fax: +603 5632 3271  
 www.dyrup.com

GORI® is a registered  
 trademark of Dyrup A/S  
 Copyright© Dyrup A/S  
 June 2009

